

~~SECRET~~
~~CONFIDENTIAL~~
NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

WARTIME REPORT

●ORIGINALLY ISSUED

April 1945 as
Memorandum Report E5D04

KNOCK-LIMITED PERFORMANCE OF SIX AROMATIC AMINES BLENDED
WITH A BASE FUEL IN A FULL-SCALE AIRCRAFT-ENGINE CYLINDER

By Anthony W. Jones, Arthur W. Bull
and Edmund R. Jonash

Aircraft Engine Research Laboratory
Cleveland, Ohio

NACA

WASHINGTON

NACA LIBRARY
LANGLEY AERONAUTICAL RESEARCH CENTER
Langley Field, Va.

NACA WARTIME REPORTS are reprints of papers originally issued to provide rapid distribution of advance research results to an authorized group requiring them for the war effort. They were previously held under a security status but are now unclassified. Some of these reports were not technically edited. All have been reproduced without change in order to expedite general distribution.

NACA MR No. E5D04

NATIONAL ADVISORY COMMITTEE FOR AERONAUTICS

MEMORANDUM REPORT

for the

Army Air Forces, Air Technical Service Command

KNOCK-LIMITED PERFORMANCE OF SIX AROMATIC AMINES

BLENDED WITH A BASE FUEL IN A FULL-SCALE

AIRCRAFT-ENGINE CYLINDER

By Anthony W. Jones, Arthur W. Bull
and Edmund R. Jonash

SUMMARY

Tests were made to investigate the effect of 2-percent additions of six aromatic amines on the knock-limited performance of 28-R fuel in a full-scale aircraft-engine cylinder. Tests were conducted with a Wright R-1820 G200 cylinder at two operating conditions with a 2-percent blend in 28-R fuel of the following six aromatic amines: N-methylxylidines (mixed isomers), N-methylcumidines (mixed isomers), N-methyltoluidines (75 percent p-, 25 percent o-), xylidines (mixed isomers), cumidines (mixed isomers from refinery cumene), and N-methylaniline (pure). Correlations of the full-scale engine data with published small-scale engine data are also presented.

The results are summarized in the following table:

RATINGS OBTAINED IN A WRIGHT R-1820 G200 CYLINDER

[For each compound there are two rows of values. The first row is imep, lb/sq in.; the second is imep ratio, which is the ratio of the imep of 98 percent 28-R fuel plus 2 percent aromatic amine to the imep of 28-R.]

Compound	Concentration in 28-R fuel ^a (percent by wt.)	Engine speed, 2000 rpm; inlet-air temperature, 210° F.			
		Spark advance, 20° B.T.C.; atmospheric exhaust pressure		Spark advance, 30° B.T.C.; exhaust pressure, 15 in. Hg absolute	
		Fuel-air ratio		Fuel-air ratio	
		0.07	0.10	0.07	0.10
N-methylxylidines (mixed isomers)	2	193 1.25	283 1.12	184 1.03	249 1.06
N-methylcumidines (mixed isomers)	2	208 1.54	290 1.15	194 1.08	259 1.10
N-methyltoluidines (75 percent p-, 25 percent o-)	2	216 1.39	288 1.14	187 1.05	260 1.10
Xylidines (mixed isomers)	2	192 1.24	280 1.11	184 1.03	257 1.09
Cumidines (mixed isomers from refinery cumene)	2	200 1.29	282 1.11	188 1.05	250 1.06
N-methylaniline (pure)	2	210 1.36	290 1.15	190 1.06	262 1.11
Base fuel (28-R)	100	155 1.00	253 1.00	179 1.00	236 1.00

^aFinal tetraethyl-lead content in blends, 4.44 ml/gal.

INTRODUCTION

A general investigation to determine the effectiveness of aromatic amines as antiknock additives for aviation fuels is being conducted at the Cleveland laboratory of the NACA at the request of the Army Air Forces, Air Technical Service Command. Two-percent blends of approximately 45 aromatic amines in 28-R fuel have been tested with an F-3 and an F-4 engine and the results are reported in references 1 to 4. The results of these tests, the physical properties of the amines (references 5 to 7), and the feasibility

of their preparation were the deciding factors in the selection of six aromatic amines for tests in a full-scale aircraft-engine cylinder.

The present report gives the results of knock tests, conducted between November 1944 and February 1945, using 2 percent of each of the six aromatic amines blended with 28-R fuel at two operating conditions in a Wright R-1820 G200 cylinder. The full-scale engine data are correlated with CFR engine data taken from references 2 to 4.

FUELS

The Organic Synthesis Section of the Fuels and Lubricants Division prepared approximately 10 pounds of each of the following unleaded aromatic amine fuels:

- N-methylxylidines (mixed isomers)
- N-methylcumidines (mixed isomers)
- N-methyltoluidines (75 percent p-, 25 percent o-)
- Xylidines (mixed isomers)
- Cumidines (mixed isomers from refinery cumene)
- N-methylaniline (pure)

The aromatic amine fuels were mixed with 28-R, which is a grade 100/130 fuel, to form blends of 2 percent aromatic amine and 98 percent base fuel by weight. Because the base fuel contains 4.53 ml TEL per gallon, the tetraethyl-lead concentration of the final aromatic amine blend was 4.44 milliliters per gallon.

APPARATUS AND TEST PROCEDURE

Apparatus. - The tests were conducted with a Wright R-1820 G200 cylinder mounted on a CUE crankcase. The auxiliary apparatus used in these tests was similar to that described in reference 8 except that a heat exchanger was installed in the cooling-air line to control the cooling-air temperature and the exhaust system was so modified that the engine could be operated either at atmospheric pressure or at a reduced exhaust pressure.

Test conditions. - The fixed engine conditions were:

Engine speed, rpm	2000
Inlet-air temperature, °F	210
Compression ratio	7.3
Oil flow to piston jets, pounds per minute	8
Oil-in temperature, °F	180 to 185
Fuel temperature at entrance to injection pump, °F	60 to 80
Cooling-air temperature, °F	85 ± 3
Spark advance, degrees B.T.C. (both plugs)	20 and 30
Exhaust pressure, inches of mercury absolute	29 ± 0.5 and 15
Valve timing:	
Intake opens, degrees B.T.C.	15
Intake closes, degrees A.B.C.	44
Exhaust opens, degrees B.B.C.	74
Exhaust closes, degrees A.T.C.	25

The cooling-air flow was determined for each test by operating the engine at a brake mean effective pressure of 140 pounds per square inch and a fuel-air ratio of 0.10 and by adjusting the dampor valve in the cooling-air line until a rear spark-plug-bushing temperature of 365° F was reached. The cooling-air pressure drop across the cylinder thus determined was maintained constant for each test.

The mixture-response curves were determined at two operating conditions: (a) simulated cruise conditions recommended by the Coordinating Research Council, which specify an engine speed of 2000 rpm, an inlet-air temperature of 210° F, a spark advance of 20° B.T.C., and atmospheric exhaust pressure; and (b) a modification of these CRC conditions that consisted in an advance spark setting of 30° B.T.C. and a reduced exhaust pressure of 15 inches of mercury absolute. The exhaust pressure of 15 inches of mercury was chosen in view of test results reported in reference 9, in which a critical relation was shown to exist between manifold and exhaust pressures and knock-limited power in the lean region where the manifold pressure is within +10 or -5 inches mercury of the exhaust pressure. The spark advance of 30° B.T.C. was chosen because of the interest in aircraft-engine operation at advanced spark under cruising conditions.

of their preparation were the deciding factors in the selection of six aromatic amines for tests in a full-scale aircraft-engine cylinder.

The present report gives the results of knock tests, conducted between November 1944 and February 1945, using 2 percent of each of the six aromatic amines blended with 28-R fuel at two operating conditions in a Wright R-1820 G200 cylinder. The full-scale engine data are correlated with CFR engine data taken from references 2 to 4.

FUELS

The Organic Synthesis Section of the Fuels and Lubricants Division prepared approximately 10 pounds of each of the following unleaded aromatic amine fuels:

- N-methylxylidines (mixed isomers)
- N-methylcumidines (mixed isomers)
- N-methyltoluidines (75 percent p-, 25 percent o-)
- Xylidines (mixed isomers)
- Cumidines (mixed isomers from refinery cumene)
- N-methylaniline (pure)

The aromatic amine fuels were mixed with 28-R, which is a grade 100/130 fuel, to form blends of 2 percent aromatic amine and 98 percent base fuel by weight. Because the base fuel contains 4.53 ml TEL per gallon, the tetraethyl-lead concentration of the final aromatic amine blend was 4.44 milliliters per gallon.

APPARATUS AND TEST PROCEDURE

Apparatus. - The tests were conducted with a Wright R-1820 G200 cylinder mounted on a CUE crankcase. The auxiliary apparatus used in these tests was similar to that described in reference 8 except that a heat exchanger was installed in the cooling-air line to control the cooling-air temperature and the exhaust system was so modified that the engine could be operated either at atmospheric pressure or at a reduced exhaust pressure.

The F-3 ratings of three of the aromatic amine fuel blends are presented in the following table, which indicates that the blend of cumidines gave the best performance when compared with N-methylcumidines and N-methylxylidines.

F-3 RATINGS OF 2-PERCENT BLENDS OF AROMATIC AMINES AND 28-R FUEL

Compound	Concentration in 28-R fuel ^a (percent by wt.)	F-3 ratings	
		S-3 + ml TEL	Performance number
28-R	100	0	100
N-methylxylidines ^b	2	.06	102
N-methylcumidines ^b	2	.04	102
Cumidines ^c	2	.13	105

^aFinal tetraethyl-lead content in blends, 4.44 ml/gal.

^bData from reference 4.

^cData from reference 3.

Correlation of Full-Scale and Small-Scale Engine Results

The correlation of the Wright R-1820 G200 cylinder data with the CFR engine data from references 2 to 4 is presented in figures 3, 4, and 5. The data in figure 3 indicate that at a fuel-air ratio of 0.07 the Wright R-1820 G200 cylinder at both operating conditions gives a higher rating to the aromatic amine blends than the F-4 engine. At a fuel-air ratio of 0.10 the F-4 data agree favorably with the R-1820 G200 data at modified CRC cruise conditions.

The correlation between the Wright R-1820 G200 cylinder data and the CFR modification A (fig. 4) is better than that with the F-4 ratings in the lean region. The agreement is good in the rich region, especially for the R-1820 G200 cylinder at CRC cruise conditions. The correlation between the data for the R-1820 G200 cylinder and the data for the CFR modification B (fig. 5) is also better than that with the F-4 engine in the lean region. In the rich region the agreement is better at the specified CRC cruise conditions than at the modified cruise conditions.

This investigation indicates that an F-4 engine run at the CFR modification A conditions gives results which more closely approximate those obtained in a full-scale aircraft-engine cylinder than either of the other two small-scale methods studied.

SUMMARY OF RESULTS

From tests to determine the antiknock effectiveness of 2-percent additions of six aromatic amines to 28-R fuel at two operating conditions in a Wright R-1820 G200 cylinder, the following results were obtained:

1. All the six aromatic amine blends increased the knock-limited power of the base fuel at both operating conditions throughout the fuel-air-ratio range.
2. At a fuel-air ratio of 0.065, the greatest increases in the knock-limited performance of the base fuel were observed with the blends of N-methyltoluidines, N-methylcumidines, and N-methylaniline at the CRC cruise conditions, and with the blends of N-methylcumidines and N-methylaniline at the modified cruise conditions.
3. At a fuel-air ratio of 0.10, N-methylcumidines, N-methyltoluidines, and N-methylaniline gave approximately the same knock-limited performance; the increase over the base fuel was greater at the CRC cruise conditions than at the modified cruise conditions.

Aircraft Engine Research Laboratory,
National Advisory Committee for Aeronautics,
Cleveland, Ohio, April 4, 1945.

REFERENCES

1. Branstetter, J. Robert: Knock-Limited Performance of Blends of AN-F-28 Fuel Containing 2 Percent Aromatic Amines - I. NACA Memo. rep., April 17, 1944.
2. Alquist, Henry E., and Tower, Leonard K.: Knock-Limited Performance of Blends of AN-F-28 Fuel Containing 2 Percent Aromatic Amines - II. NACA Memo. rep., June 26, 1944.
3. Alquist, Henry E., and Tower, Leonard K.: Knock-Limited Performance of Blends of AN-F-28 Fuel Containing 2 Percent Aromatic Amines III. NACA Memo. rep., Aug. 23, 1944.
4. Alquist, Henry E., and Tower, Leonard K.: Knock-Limited Performance of Blends of AN-F-28 Fuel Containing 2 Percent Aromatic Amines - IV. NACA MR No. E4L21, Dec. 21, 1944.

5. Olson, Walter T., and Kelly, Richard L.: The Low-Temperature Solubility of Aniline, Toluidines, and Some of Their N-Alkyl Derivatives in Aviation Gasoline. NACA Memo. rep., June 5, 1944.
6. Olson, Walter T., Tischler, Adelbert O., and Goodman, Irving A.: Gasoline-Water Distribution Coefficients of 27 Aromatic Amines. NACA Memo. rep., Aug. 3, 1944.
7. Kelly, Richard L.: The Low-Temperature Solubility of 24 Aromatic Amines in Aviation Gasoline. NACA MR No. E4K17, Nov. 17, 1944.
8. Jones, Anthony W., and Bull, Arthur W.: Knock-Limited Performance of Pure Hydrocarbons Blended with a Base Fuel in a Full-Scale Aircraft-Engine Cylinder. I - Eight Paraffins, Two Olefins. NACA ARR No. E4E25, 1944.
9. Cook, Harvey A., Held, Louis F., and Pritchard, Ernest I.: The Influence of Exhaust Pressure on Knock-Limited Performance. NACA MR No. E5A05, Army Air Forces, Jan. 5, 1945.

TABLE I - COMPARISON OF RATINGS OBTAINED IN A WRIGHT R-1820 G200 CYLINDER WITH CFR ENGINE RATINGS

[For each compound there are two rows of values. The first row is imep, lb/sq in.; the second is imep ratio, which is the ratio of the imep of 98 percent 28-R fuel plus 2 percent aromatic amine to the imep of 28-R.]

Compound	Concentration in 28-R fuel ^a (percent by wt.)	CFR engine ratings						Wright R-1820 G200 ratings (Engine speed, 2000 rpm; inlet-air temperature, 210° F; compression ratio, 7.3)										Boiling point of amine (°F)
		F-4 (inlet-air temperature, 225° F; spark advance, 45° B.T.C.)		Modification A (inlet-air temperature, 250° F; spark advance, 30° B.T.C.)		Modification B (inlet-air temperature, 150° F; spark advance, 30° B.T.C.)		Spark advance, 20° B.T.C.; exhaust pressure, 29 ±0.5 in. Hg absolute					Spark advance, 30° B.T.C. exhaust pressure, 15 in. Hg absolute					
		Fuel-air ratio		Fuel-air ratio		Fuel-air ratio		Fuel-air ratio					Fuel-air ratio					
		0.07	0.10	0.07	0.10	0.07	0.10	0.065	0.07	0.08	0.09	0.10	0.065	0.07	0.08	0.09	0.10	
N-methylxylidines (mixed isomers)	2	b1.03	b1.05	b1.05	b1.10	b1.13	b1.10	1.64	1.93	2.22	2.56	2.83	1.73	1.84	2.09	2.32	2.49	426 - 446
N-methylcumidines (mixed isomers)	2	b0.98	b1.11	b1.11	b1.17	b1.16	b1.14	1.95	2.08	2.45	2.72	2.90	1.82	1.94	2.20	2.45	2.59	450 - 468
N-methyltoluidines (75% p-, 25% o-)	2	-----	-----	-----	-----	-----	-----	1.95	2.16	2.44	2.75	2.88	1.78	1.87	2.04	2.39	2.60	405 - 415
Xylidines (mixed isomers)	2	-----	-----	-----	-----	-----	-----	1.72	1.92	2.30	2.57	2.80	1.73	1.84	2.14	2.37	2.57	416 - 429
Cumidines (from refinery cumene - mixed isomers)	2	c1.02	c1.04	c1.10	c1.07	c1.09	c1.11	1.84	2.00	2.37	2.57	2.82	1.73	1.88	2.15	2.32	2.50	428 - 442
N-methylaniline	2	d0.99	d1.10	d1.15	d1.13	d1.13	d1.11	1.92	2.10	2.40	2.69	2.90	1.81	1.90	2.18	2.40	2.62	381 - 385
Base fuel (28-R)	100	1.00	1.00	1.00	1.00	1.00	1.00	1.41	1.55	2.09	2.35	2.53	1.66	1.79	2.03	2.26	2.36	-----


^a Final tetraethyl-lead content in blends, 4.44 ml/gal.

^b Data from reference 4.

^c Data from reference 3.


^d Data from reference 2.

NATIONAL ADVISORY COMMITTEE
FOR AERONAUTICS




(a) Fuels, 28-R, N-methylxylidines, N-methylcumidines, and N-methyltoluidines (75-percent p-, 25-percent o-).

Figure 1. - Knock-limited performance of blends of 28-R fuel containing 2-percent aromatic amines at atmospheric exhaust pressure and a spark advance of 20° B.T.C. Wright R-1820 G200-cylinder; engine speed, 2000 rpm; inlet-air temperature, 210° F; compression ratio, 7.3; cooling air adjusted at 140 bmeq and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 365° F.




(b) Fuels, 25-R, xylydines, cumidines, and N-methylaniline.

Figure 1. - Concluded. Knock-limited performance of blends of 25-R fuel containing 2-percent aromatic amines at atmospheric exhaust pressure and a spark advance of 20° B.T.C. Wright R-1820 G800-cylinder; engine speed, 2000 rpm; inlet-air temperature, 210° F; compression ratio, 7.3; cooling air adjusted at 140 bwp and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 805° F.



(a) Fuels, 28-R, N-methylxylidines, N-methylcumidines, and N-methyltoluidines (75-percent p-, 25-percent o-).

Figure 2. - Knock-limited performance of blends of 28-R fuel containing 2-percent aromatic amines at an exhaust pressure of 15 inches of mercury absolute and a spark advance of 30° B.T.C. Wright R-1820 G200 cylinder; engine speed, 2000 rpm; inlet-air temperature, 210° F; compression ratio, 7.3; cooling air adjusted at 140 bmeq and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 365° F.



(b) Fuels, 28-R, xylydines, cumidines, and N-methylaniline.

Figure 2. - Concluded. Knock-limited performance of blends of 28-R fuel containing 2-percent aromatic amines at an exhaust pressure of 15 inches of mercury absolute and a spark advance of 30° B.T.C. Wright R-1820 3200 cylinder; engine speed, 2000 rpm; inlet-air temperature, 210° F; compression ratio, 7.3; cooling air adjusted at 140 bmep and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 365° F.




Figure 4. - Correlation of Wright R-1820 G200 engine data with CFR modification A engine data. Wright R-1820 G200 conditions: engine speed, 2000 rpm; compression ratio, 7.3; inlet-air temperature, 210° F; cooling air adjusted at 140 bmeq and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 365° F. CFR modification A conditions: inlet-air temperature, 250° F; spark advance, 30° B.T.C.; coolant temperature, 250° F.




Figure 5. - Correlation of Wright R-1820 G200 engine data with CFR modification B engine data. Wright R-1820 G200 conditions: engine speed, 2000 rpm; compression ratio, 7.3; inlet-air temperature, 210° F; cooling air adjusted at 140 bme and 0.10 fuel-air ratio to give a rear spark-plug-bushing temperature of 365° F. CFR modification B conditions: inlet-air temperature, 150° F; spark advance, 30° B.T.C.; coolant temperature, 250° F.

LANGLEY RESEARCH CENTER



3 1176 01364 8242